

SCHEDA TECNICA
Data Sheet
CSCL - KAOLINSCHAMOTTE
CSCL - Kaolinchamotte

Umidità media / massima: 0.1% / 0.5%

moisture med/max

Analisi chimica <i>chemical analysis</i>	Min <i>Min</i>	Tipica <i>typical</i>	Max <i>Max</i>
SiO ₂	54.0 %	55.0 %	56.0 %
Al ₂ O ₃	41.0 %	42.40 %	43.0 %
Fe ₂ O ₃	0.35 %	0.40 %	0.55 %
TiO ₂	0.25 %	0.35 %	0.45 %
CaO		0.05 %	0.15 %
MgO		0.10 %	0.25 %
Na ₂ O		0.10 %	0.15 %
K ₂ O	1.20 %	1.30 %	1.50 %
P.F.		0.10 %	

Granulometria
particle size

> 500 µm 3 % max

Composizione mineralogica
Mineralogical composition

Quarzo <i>Quartz</i>	2
Mullite <i>Mullite</i>	45
Fasi vetrose <i>Glass phases</i>	53

Firma:
Signature:


Ed. 8 del 13-04-2017

 La presente annulla e sostituisce le precedenti
The present act cancels and overrides the previous

Pag.nr.

1